# Spray Star 5200



#### Specifications

Engine	
Туре	Kubota WG3800 Gas Engine
Displacement	230cu.in. (3.769L)
Rated Horsepower	87 hp (65 kW) @3000 RPM
Air Cleaner	Double Action air intake filtration
Cooling	Liquid cooled
Lubrication	Full Pressurized
Oil Filter	Full flow, spin on type
Electrical System	60 amp, with 12V 900 CCA battery, fuse
	protected
Fuel Capacity	20 gallons (75.7 l) Unleaded
Traction Drive	
Traction System	Hydraulic power to two rear wheel drive
	planetary motors
Hydraulic System	10 gallons (37.8 l)
Hydraulic Cooling	Full flow filter with oil
Tires, Brakes and Stee	ring
Tires	Front: 27-10.50x15 Turf
	Rear: 33/16.00xLL500 Multi trac
Service Brakes	Dynamic braking through hydrostatic
	transmission
Parking Brake	Auto spring pressure release park brake
Steering	Hydraulic Power Steering with orbital
	motor. 15" steering wheel with tilt
	adjustment
Spray Tank	530 million = (4000 l)
Capacity	520 gallons (1968 I)
Construction	
	Fiber reinforced polystyrene with UV
	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in
Eiltration	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in locking device and nylon strainer basket
Filtration	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in locking device and nylon strainer basket Downstream filtration 50 or 80 mesh
	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in locking device and nylon strainer basket Downstream filtration 50 or 80 mesh strainer
Agitation	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in locking device and nylon strainer basket Downstream filtration 50 or 80 mesh strainer  Agitator with 4 venturi volume boosters
	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in locking device and nylon strainer basket Downstream filtration 50 or 80 mesh strainer  Agitator with 4 venturi volume boosters  Rocker switch operated. Stainless, high-
Agitation	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in locking device and nylon strainer basket Downstream filtration 50 or 80 mesh strainer  Agitator with 4 venturi volume boosters  Rocker switch operated. Stainless, highvolume, 4-stage, centrifugal with silicon
Agitation Pump	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in locking device and nylon strainer basket Downstream filtration 50 or 80 mesh strainer  Agitator with 4 venturi volume boosters  Rocker switch operated. Stainless, high-
Agitation Pump Spray Performance	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in locking device and nylon strainer basket Downstream filtration 50 or 80 mesh strainer  Agitator with 4 venturi volume boosters  Rocker switch operated. Stainless, high-volume, 4-stage, centrifugal with silicon carbide seals. 10-130 psi (0-8.96 bar).
Agitation Pump	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in locking device and nylon strainer basket Downstream filtration 50 or 80 mesh strainer  Agitator with 4 venturi volume boosters  Rocker switch operated. Stainless, highvolume, 4-stage, centrifugal with silicon
Agitation Pump Spray Performance	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in locking device and nylon strainer basket Downstream filtration 50 or 80 mesh strainer  Agitator with 4 venturi volume boosters  Rocker switch operated. Stainless, highvolume, 4-stage, centrifugal with silicon carbide seals. 10-130 psi (0-8.96 bar).  20-220 gallons(180 – 2050 I) per acre
Agitation Pump  Spray Performance Application Rates  Production Rate	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in locking device and nylon strainer basket  Downstream filtration 50 or 80 mesh strainer  Agitator with 4 venturi volume boosters  Rocker switch operated. Stainless, highvolume, 4-stage, centrifugal with silicon carbide seals. 10-130 psi (0-8.96 bar).  20-220 gallons(180 – 2050 l) per acre  0.5-5 gallons per 1000 sq.ft.
Agitation Pump  Spray Performance Application Rates	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in locking device and nylon strainer basket  Downstream filtration 50 or 80 mesh strainer  Agitator with 4 venturi volume boosters  Rocker switch operated. Stainless, highvolume, 4-stage, centrifugal with silicon carbide seals. 10-130 psi (0-8.96 bar).  20-220 gallons(180 – 2050 l) per acre  0.5-5 gallons per 1000 sq.ft.
Agitation Pump  Spray Performance Application Rates  Production Rate Sound & Speed	Fiber reinforced polystyrene with UV inhibitors. 16" hinged lid with built in locking device and nylon strainer basket Downstream filtration 50 or 80 mesh strainer  Agitator with 4 venturi volume boosters Rocker switch operated. Stainless, high-volume, 4-stage, centrifugal with silicon carbide seals. 10-130 psi (0-8.96 bar).  20-220 gallons(180 – 2050 l) per acre 0.5-5 gallons per 1000 sq.ft. 6.4 acres/hour @ 3.5 mph (5.6 kph)

Weights and Dimensions	
Weight	Dry - 4155 lbs (1884 kg)
	Loaded – 8491 lbs (3851 kg)
Length	174" (4.42m)
Width	89" (2.26m)
Height	84" (2.13m)
Wheelbase	88" (1.24m)

## **Product Configuration**

Spray Star 5200

- ✓ Leaf spring front suspension
- ✓ Passenger seat
- ✓ Choice of electric or computer spray control system
- ✓ Smithco Engineered ROPs with seat belts

### Spray Systems 5200

	20' or 24' Super Boom
	5287 Star Command I TeeJet® Radion 8140
	and DynaJet System with 20' boom
	5288 Star Command I TeeJet® Radion 8140
	and DynaJet System with 24' boom
	5285 Star Command II Teejet® Aeros GPS
	Satellite System with 20' boom
	5286 Star Command II Teejet® Aeros GPS
	Satellite System with 24' boom
	5220 Radion 8140 with 20' Boom
	5224 Radion 8140 with 24' Boom
	1-Year Terra Star Subscription
	3-Year terra Star Subscription

# Spray Star 5200 Shigh Star School



#### **Accessories**

□ Water Fill Meter Kit - gallons or liters
 □ Foam Marker - electric operation, manual control
 □ Manual hose Reel – 200' (61m)
 □ Electric Hose Reel – 200' (61m)
 □ 30 gallon(98l) Wash Tank System
 □ Fresh Water Wash Tank
 □ Chemical Cleanload Safe fill System
 □ Tank Rinse System
 □ 3/4" or 5/8" Pressure Hose Kits in 50', 100' or 200' lengths
 □ Pistol Grip JD9 Spray Gun
 □ Field Pilot Auto steer
 □ Rear View Camera