

Smithco

Sand Star CVT Specifications



ENGINE

Type	Briggs & Stratton Model 19L237
Rated Horsepower	10 HP (7.46kW)
Air Cleaner	Engine mounted
Cooling	Air-cooled
Electrical System	10 Amp
Fuel Capacity	3.8 qts. (3.6L), minimum 87 octane

TRACTION DRIVE

Traction System	Dana CVT (Constant Velocity Transmission), two wheel drive, forward / reverse drive pedals at operator's station
Forward Speed	0 to 12 m.p.h. (0-19 kph)
Reverse Speed	0 to 5 m.p.h. (0-8 kph)
Engine Throttle	Foot operated at operator's station
Wheels & Tires	Front 20x10-10 turf tires Rear 25x10-12 turf tires
Service Brakes	Mechanical drum type
Parking Brake	Lever controlled
Steering	Manual chain drive

REAR MOUNTED IMPLEMENTS	Electric over hydraulic control standard. Smithco "classic" hitch requires an "A" on rear implements versus a "Q"
--------------------------------	---

CENTER MOUNTED IMPLEMENTS	Manual control standard. Implement part numbers: 41-021 sand cultivator, 41-022 spring tine sand cultivator, 41-023 infield scarifier
----------------------------------	---

FRONT MOUNTED IMPLEMENT	40" (102cm) manually operated plow, aluminum blade Implement part number 13-644
--------------------------------	--

WEIGHTS & DIMENSIONS

Length / Width / Height	68" (1.73m), 61" (1.55m), 50" (1.3m)
Wheelbase	51" (1.3m)
Ground Clearance	5.5" to 7" (13-18cm)
Weight	841 lbs. (381kg)
Ear Sound Level	85 dB